

Mix Inside Closed Shipping Cans

>> [Click to Watch Video](#) <<

- Efficient “corner-over-corner” tumbling action
- Use common 1 to 5 gallon pails for mixing

- Use separate can for each batch
- No container to purge between batches

Model 1-305-1 shown



Single Can Tumblers rotate one can “corner-over-corner”

Model 2-305-1 shown



Double Can Tumblers rotate one or two cans at a time

PailPRO™ Can Tumblers

Rotate your cans or pails thoroughly blend ingredients with an efficient “corner-over-corner” mixing action. Morse Can Tumblers are perfect to mix or blend small batches... or you can tumble parts with media to polish or deburr.

Mixing in ordinary pails, instead of using special containers or insertion mixers, saves time and money! There is no costly transfer and no messy clean-up. It reduces the possibility of spills and the hazards of worker exposure to the product.

The cans are held at an angle to the horizontal rotating shaft to provide a thorough “corner-over-corner” mixing action. Quickly secure a can in the holder with the adjustable bottom cross bar and screw-down top bar with locking handle. A 1/4 HP motor provides plenty of power for long service. It rotates the pail at a constant 23 RPM (19 RPM on 50Hz models) in one direction – the unit does not shake or oscillate cans. The heavy-duty steel frame stands steady while tumbling.

Can Dimensions: 4.5" to 16.5" (11.4 to 42 cm) tall
 Up to 12.5" (31.75 cm) in diameter

Can Speed: 23 RPM on 60Hz models
 19 RPM on 50Hz models

Capacity: 100 Lb. (45 kg) per can

Motor: AC Single or 3 phase, 60 or 50 Hz
 Explosion proof available
 Air powered models available

Domestic ship dimensions: L42" W42" H34" (107 x 107 x 86 cm)

Ship Class: 70

The single phase, 115V models (models 1-305-1 and 2-305-1) are equipped with an adjustable timer. This allows the operator to select a running time up to 60 minutes with automatic shut-off. Other motor types do not include timer, cord or plug, and must be wired according to your local codes by a qualified electrician.

Enclosures with Safety Interlock

>> [Click to Watch Video](#) <<



Guard Enclosure shown installed with Double Can Tumbler (Can Tumbler sold separately).

Install all Morse Can Tumblers and drum rotators in accordance with OSHA requirements for enclosure with interlock, etc. For OSHA compliance, see OSHA subpart O.1910.212(a)(4) “Barrels, containers, and drums. Revolving drums, barrels, and containers shall be guarded by an enclosure which is interlocked with the drive mechanism, so that the barrel, drum, or container cannot revolve unless the guard enclosure is in place.”

Power connections and motor controls must comply with applicable codes.

Can Tumbler Model Numbers

Model #	Rotates	Motor	Volts AC	Hz	Phase	Full Load Amp Draw	Domestic Ship Weight
2-305-1	1 or 2 cans at 23 RPM	1/4 HP TEFC with 1 to 60 minute timer	115V	60	1	5.0	205 Lb. (93 kg)
2-305-1-50	1 or 2 cans at 19 RPM	1/2 HP TEFC	110 / 220V	50	1	7.2 / 3.6	205 Lb. (93 kg)
2-305-1-230	1 or 2 cans at 23 RPM	1/4 HP TEFC	208 / 230V	60	1	3.0 / 2.5	205 Lb. (93 kg)
2-305-3	1 or 2 cans at 23 RPM	1/4 HP TEFC	208-230 / 460V	60	3	1.7 / 1.3 / .7	205 Lb. (93 kg)
2-305-3-50	1 or 2 cans at 19 RPM	1/4 HP TENV	190 / 380V	50	3	1.2 / .6	205 Lb. (93 kg)
2-305-575	1 or 2 cans at 23 RPM	1/2 HP TEFC	575V	60	3	.8	205 Lb. (93 kg)
2-305-A	1 or 2 cans at 23 RPM	1/4 HP Air motor **	-	-	-	-	190 Lb. (86 kg)
2-305-E1	1 or 2 cans at 23 RPM	1/4 HP Explosion proof *	115 / 208-230V	60	1	5.0 / 2.6-2.5	210 Lb. (95 kg)
2-305-E1-50	1 or 2 cans at 19 RPM	1/4 HP Explosion proof *	110 / 220V	50	1	5.2 / 2.6	210Lb. (95 kg)
2-305-E3	1 or 2 cans at 23 RPM	1/4 HP Explosion proof *	208-230 / 460V	60	3	1.4-1.3 / .7	231 Lb. (105 kg)
2-305-E3-50	1 or 2 cans at 19 RPM	1/2 HP Explosion proof *	230 / 400V	50	3	1.7 / 1.0	231 Lb. (105 kg)
2-305-E575	1 or 2 cans at 23 RPM	1/2 HP Explosion proof *	575V	60	3	.7	231 Lb. (105 kg)
1-305-1	1 can at 23 RPM	1/4 HP TEFC with 1 to 60 minute timer	115V	60	1	5.0	175 Lb. (80 kg)
1-305-1-50	1 can at 19 RPM	1/2 HP TEFC	110 / 220V	50	1	7.2 / 3.6	175 Lb. (80 kg)
1-305-1-230	1 can at 23 RPM	1/4 HP TEFC	208 / 230V	60	1	3.0 / 2.5	175 Lb. (80 kg)
1-305-3	1 can at 23 RPM	1/4 HP TEFC	208-230 / 460V	60	3	1.7 / 1.3 / .7	155 Lb. (70 kg)
1-305-3-50	1 can at 19 RPM	1/4 HP TENV	190 / 380V	50	3	1.2 / .6	155 Lb. (70 kg)
1-305-575	1 can at 23 RPM	1/2 HP TEFC	575V	60	3	.8	155 Lb. (70 kg)
1-305-A	1 can at 23 RPM	1/4 HP Air motor **	-	-	-	-	155 Lb. (70 kg)
1-305-E1	1 can at 23 RPM	1/4 HP Explosion proof *	115 / 208-230V	60	1	5.0 / 2.6-2.5	180 Lb. (82 kg)
1-305-E1-50	1 can at 19 RPM	1/4 HP Explosion proof *	110 / 220V	50	1	5.2 / 2.6	180 Lb. (82 kg)
1-305-E3	1 can at 23 RPM	1/4 HP Explosion proof *	208-230 / 460V	60	3	1.4-1.3 / .7	180 Lb. (82 kg)
1-305-E3-50	1 can at 19 RPM	1/2 HP Explosion proof *	230 / 400V	50	3	1.7 / 1.0	180 Lb. (82 kg)
1-305-E575	1 can at 23 RPM	1/2 HP Explosion proof *	575V	60	3	.7	180 Lb. (82 kg)

* Explosion proof motors are rated for class I group D and class II groups F and G.

** Air powered models require plant air at 40 psi and flowing at a rate of 22 scfm. Filter, Regulator, Lubricator and valve (part # 90010-P) should be installed in the air line ahead of the motor.

MADE
IN
USA

Options to Mix Larger Cans

Options to Mix Larger Cans

include a raised base and larger can holder(s) to accommodate a can:

- Up to 16" (40.6 cm) diameter
- 11" to 22" (28 to 55.9 cm) tall
- Capacity: 100 Lb. (45.5 kg) per can

IMPORTANT NOTE: These Options REQUIRE larger enclosures than standard can tumblers.

- GEK-XLC-1-305 Series
- GEK-XLC-2-305 Series

Option XLC-1-305



Option XLC-2-305



Single Can Tumbler shown with option to mix a larger can installed. Option XLC-1-305 includes a raised base for the Can Tumbler and 1 larger can holder.

Double Can Tumbler shown with option to mix two larger cans installed. Option XLC-2-305 includes a raised base for the Can Tumbler, and 2 larger can holders

Options to Mix Larger Cans

Option #	Install on	Description	Maximum Can Diameter	Can Height	Maximum Can Weight	Domestic Ship Weight	Domestic Ship Dimensions
XLC-1-305	1-305 Series	Option for larger can on Single Can Tumbler	16" (40.64 cm)	11" to 22" (28 to 55.9 cm)	100 Lb. (45.4 kg)	68 Lb. (30.8 kg)	
XLC-2-305	2-305 Series	Option for larger cans on Double Can Tumbler	16" (40.64 cm)	11" to 22" (28 to 55.9 cm)	100 Lb. (45.4 kg)	106 Lb. (48.1 kg)	

Larger Guard Enclosure Kits and Interlock for Tumbler with XLC Option Installed

Model #	Fits Model # with XLC Option	Description	Domestic Ship Weight	Domestic Ship Dimensions
GEK-XLC-1-305-1	1-305-1	Larger Enclosure for 1-305-1 with XLC Option	350 Lb. (159 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-1-305-3	1-305-3	Larger Enclosure for 1-305-3 with XLC Option	350 Lb. (159 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-1-305-A	1-305-A	Larger Enclosure for 1-305-A with XLC Option	350 Lb. (159 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-1-305-E1	1-305-E1	Larger Enclosure for 1-305-E1 with XLC Option	350 Lb. (159 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-1-305-E3	1-305-E3	Larger Enclosure for 1-305-E3 with XLC Option	350 Lb. (159 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-2-305-1	2-305-1	Larger Enclosure for 2-305-1 with XLC Option	360 Lb. (163 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-2-305-3	2-305-3	Larger Enclosure for 2-305-3 with XLC Option	360 Lb. (163 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-2-305-A	2-305-A	Larger Enclosure for 2-305-A with XLC Option	360 Lb. (163 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-2-305-E1	2-305-E1	Larger Enclosure for 2-305-E1 with XLC Option	360 Lb. (163 kg)	L101" W31" H66" (257 x 79 x 168 cm)
GEK-XLC-2-305-E3	2-305-E3	Larger Enclosure for 2-305-E3 with XLC Option	360 Lb. (163 kg)	L101" W31" H66" (257 x 79 x 168 cm)

MADE IN USA