


IMPORTANT
THIS PANEL IS DESIGNED FOR SINGLE-PHASE LINE-TO-LINE (L1,L2)
[FOR CONNECTION TO SINGLE-PHASE LINE-NEUTRAL (L,N) SUPPLY,
CONNECT L TO L1 AND N TO L2]



TIMER SETTINGS		
PARAMETER	DISPLAY	SETTING
Output operation mode	oLk n	o n d
Time Range	t r n G	99'59 ^m
Time UP/DOWN	U d	d n
Width of min. input signal	i n k	20
Backlight	b L U	o n
Key lock	L o c k	L o F F

150
152
153
154
155
156
157
158
159
160
162
163
164
165
166
167
168
169
170
172
173
174
175
176
177
178
179
180
182
183
184
185
186
187
188
189
190
192
193
194
195
196
197
198
199



PCV PCW MORSE <i>The Specialist In Drum Handling Equipment</i> 103 Kuhn Rd, Syracuse, NY 13208 TEL: 315-654-4347 FAX 315-437-1029	PCV PCW MORSE <i>The Specialist In Drum Handling Equipment</i> 103 Kuhn Rd, Syracuse, NY 13208 TEL: 315-654-4347 FAX 315-437-1029	PCV PCW MORSE <i>The Specialist In Drum Handling Equipment</i> 103 Kuhn Rd, Syracuse, NY 13208 TEL: 315-654-4347 FAX 315-437-1029	PCV PCW MORSE <i>The Specialist In Drum Handling Equipment</i> 103 Kuhn Rd, Syracuse, NY 13208 TEL: 315-654-4347 FAX 315-437-1029
--	--	--	--