



80A SERIES

SPECIFICATIONS SHEET

- Self Supporting... No weight in operator's hands**
- Lock drum upright to transport, horizontal to dispense**
- When unlocked, grasp drum to tilt to any angle**
- Turn 360° to mix contents**
- Capacity: 800 Lb. (363 kg)**

Mobile-Karrier is More than a Drum Truck

Many features make it more versatile and convenient!

Supports full drum weight when transporting upright to avoid spills. Ratcheting handle locks prevent unintentional lowering of drum. Use tilt-locks on each side to keep drum upright or horizontal. Locked at horizontal, drum remains steady for dispensing. When unlocked, grasp drum to tilt by hand for pouring, or turn end-over-end to mix contents.

Easy to maneuver on 8" (20.3 cm) hard polyolefin roller bearing front wheels, and 4" (10.2 cm) ball-bearing swivel caster. Welded structural steel frame for long service.

Made at our single factory in Syracuse, New York U.S.A. Ships partly assembled in durable carton to save you freight costs.

MOBILE-KARRIERS



High Strength Lifting Components

Solid steel band around drum has MORSE name boldly cut through it, permanently identifying it as a genuine, quality Morse product.

High strength, wear resistant cinch chain secures around drum. Chain tightening ratchet and spring loaded pawl assembly has been designed with oversize, specially contoured teeth and redundant safety features for reliability and ease of use.

Model	Description	Handle Types of Drums
80A	Mobile-Karrier with cinch chain drum holder	Steel 55-gallon (210 liter) drum 22.5" (57 cm) diameter between ribs
80AM	Mobile-Karrier with cinch chain drum holder and spark resistant parts	Steel 55-gallon (210 liter) drum 22.5" (57 cm) diameter between ribs
80APS	Mobile-Karrier with cinch chain drum holder for 55-gallon (210 liter) plastic or steel drum	55-gallon (210 liter) plastic drum 22.5" to 24" (57 to 61 cm) diameter, 34" to 36" (86 to 92 cm) tall. Also standard steel 55-gallon (210 liter) drum.

Advanced design. Improved safety features.

- Simple to lift, move, tilt, agitate and dispense a heavy drum
- **Adjustable Leverage** - Adjust Morse Mobile-Karrier to do job with minimum effort. Adjust to accommodate drum weights up to 800 Lb. (363 kg) and floor clearances of 5-1/8" to 11" (13 to 27.9 cm). Tipping capacities vary with type and amount of load carried.
- **Model 80AM has Spark Resistant Parts** - Spark resistant model is made with Monel drum holder band. The letter "M" in model 80AM designates the unit is made with spark resistant parts. Stainless steel cinch chain replaces the standard steel chain.



1.

1. SIMPLE TO SECURE DRUM

Roll Mobile-Karrier forward and push drum holder into center of drum. Secure cinch chain across front of drum with the ratchet tightener. No tools are necessary.



2.

2. JUST PULL DOWN HANDLE TO RAISE DRUM

Raise drum by squeezing the two handle release rods and pull handle downward. Automatic locks engage to hold drum up as handle is lowered. Tilt locks hold drum upright.



3.

3. EASY TO MOVE WITHOUT SPILLING CONTENTS

Mobile-Karrier supports load so operator can quickly and easily move drum to dispensing area. Always transport drum in upright position to avoid spilling.



4.

4. DISPENSE FROM ANY POSITION

Grasp drum to tilt by hand. Set tilt locks to secure drum at horizontal or at 45° for dispensing, or release tilt locks to allow drum turning. May be left holding drum for subsequent dispensing.

DIMENSIONS

FOR DRUM WITH 22-1/2" (57.2 cm) DIAMETER, 36" (91.4 cm) TALL

