



22" (56 cm)  
Outside Diameter



23.5" (59.7 cm)  
Outside Diameter

# MORSE MORCINCH™


## SPECIFICATIONS SHEET

## MORCINCH™ DRUM HANDLING SYSTEM

### Handle almost any drum

MORCINCH™ Drum Handling System is featured on many of our below-hook, forklift and mobile drum pourers.

MORCINCH™ Drum Holder **Automatically Adjusts** for 22" to 23.5" (56 to 59.7 cm) diameter. It has flexible cinch chain cover to help grip and protect drum sidewall. Alloy cinch chain and hinge, and stress relief weld joints increase durability. Web Strap Option 5115i-P replaces cinch chain around drum (NOT for spark resistant models).



### MORCINCH™ Kits and Accessories

- Install Top Rim Clamp for RIMMED plastic drum
- Install Bracket Assembly for RIMLESS plastic drum
- Insert correct Diameter Adapter for each smaller size drum


#### Top Rim Clamp Kit



Install Top Rim Clamp to safely handle RIMMED 30 or 55 gallon plastic drum. Grips top rim to prevent drum from slipping length-ways. Must install either Top Rim Clamp or Bracket Assembly to safely handle plastic drum.

Kit	Description
4560B-P	Top Rim Clamp
4560BM-P	Spark Resistant
4560BSS-P	Stainless Steel


#### Bracket Assembly Kit



Required for RIMLESS plastic drum and more securely holds fiber drum. For 30 to 55-gallon (114 to 210 liter) plastic, steel or fiber drum. Prevents drum from slipping length-ways. Adjust for 31" to 39" (78.7 to 99 cm) tall drum.

Kit	Description
4556-P	Bracket Assembly
4556M-P	Spark Resistant
4556SS-P	Stainless Steel

#### Diameter Adapters



Diameter Adapters enable handling a smaller drum with the same drum handler. Insert correct size Diameter Adapter for smaller drum. Then remove Diameter Adapter to return to 55-gallon (210 liter) drum.

Some Diameter Adapters have integrated brackets at top and bottom of drum. Adjust brackets to securely hold drum up to 38" (96.5 cm) tall.

Measure outside diameter halfway down drum between ribs, where Diameter Adapter engages.

Diameter Adapter	Spark Resistant	Stainless Steel	Has Brackets	Fits Diameter
55/30-20.5	55/30M-20.5	55/30SS-20.5	No	20" to 20.5" (50.8 to 52.1 cm)
55/30-19	55/30M-19	55/30SS-19	No	18.5" to 19" (47 to 48.3 cm)
55/30-19B	55/30M-19B	55/30SS-19B	Yes	18.5" to 19" (47 to 48.3 cm)
55/30-17.5	55/30M-17.5	55/30SS-17.5	Yes	17" to 17.5" (43.2 to 44.5 cm)
55/30-16	55/30M-16	55/30SS-16	Yes	15.5" to 16" (39.4 to 40.6 cm)
55/30-14.5	55/30M-14.5	55/30SS-14.5	Yes	14" to 14.5" (35.6 to 36.8 cm)